

SAFETY DATA SHEET



SP3749 Thinner Medium

Section 1. Identification

Product name : SP3749 Thinner Medium

Product type : Liquid.

Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Use in coatings - Thinner.

Supplier

Manufacturer : Valspar b.v.
Zuiveringweg 89
8243 PE Lelystad
The Netherlands
tel: +31 (0)320 292200
fax: +31 (0)320 292201

Emergency telephone number : Call: +31 (0)320 292200 (during daytime)

Supplier's details : DBNZ Coatings Limited
6 Killarney Lane
Hamilton 3243
NEW ZEALAND
T: +64 7847 0933
F: +64 7847 0932
E: info@dbnz.co.nz

Emergency telephone number (with hours of operation) : New Zealand Poisons Information Centre: 0800 764766 (24 hrs)

e-mail address of person responsible for this SDS : info.nl@valspar.com

Section 2. Hazards identification

HSNO Classification : 3.1 - FLAMMABLE LIQUIDS - Category B
6.1 - ACUTE TOXICITY (oral) - Category D
6.3 - SKIN IRRITATION - Category A
6.4 - EYE IRRITATION - Category A (Irritant)
6.7 - CARCINOGENICITY - Category B
6.8 - REPRODUCTIVE AND DEVELOPMENTAL TOXICITY (Fertility) - Category B
6.8 - REPRODUCTIVE AND DEVELOPMENTAL TOXICITY (Unborn child) - Category B
6.9 - SPECIFIC TARGET ORGAN TOXICITY (SINGLE OR REPEATED EXPOSURE) - Category B
6.1 - ACUTE TOXICITY (aspiration) (oral) - Category E
9.1 - AQUATIC ECOTOXICITY - Category B

This material is classified as hazardous according to criteria in the Hazardous Substances (Minimum Degrees of Hazard) Regulations 2001 and has been classified according to the Hazardous Substances (Classifications) Regulations 2001.

This material is classified as DANGEROUS GOODS according to criteria in New Zealand Standard 5433:2012 Transport of Dangerous Goods on Land.

GHS label elements

Signal word : Danger

Section 2. Hazards identification

Hazard statements : Highly flammable liquid and vapour.
Harmful if swallowed.
Causes skin irritation.
Causes serious eye irritation.
Suspected of causing cancer.
Suspected of damaging fertility or the unborn child.
May be fatal if swallowed and enters airways.
May cause damage to organs.
Toxic to aquatic life with long lasting effects.

Precautionary statements

Prevention : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Wear protective gloves. Wear eye/face protection. Keep away from ignition sources such as heat/sparks/open flame. - No smoking. Use explosion-proof electrical, ventilating, lighting and all material-handling equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Keep container tightly closed. Avoid release to the environment. Do not breathe vapour or spray. Do not eat, drink or smoke when using this product. Wash thoroughly after handling.

Response : Collect spillage. Immediately call a POISON CENTER or doctor/physician. IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Take off contaminated clothing and wash before reuse. Rinse skin with water/shower. Wash with plenty of soap and water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical advice/attention.

Storage : Store locked up. Store in a well-ventilated place. Keep cool.

Disposal : Dispose of contents and container in accordance with all local, regional, national and international regulations.

Symbol :



Other hazards which do not result in classification : None known.

Section 3. Composition/information on ingredients

Substance/mixture : Mixture

Ingredient name	% (w/w)	CAS number
n-butyl acetate	25 - 50	123-86-4
Solvent naphtha (petroleum), light arom.	12.5 - 25	64742-95-6
xylene	12.5 - 25	1330-20-7
1,2,4-trimethylbenzene	5 - 12.5	95-63-6
acetone	5 - 12.5	67-64-1
Solvent naphtha (petroleum), heavy arom.	1 - 5	64742-94-5
ethylbenzene	1 - 5	100-41-4
mesitylene	1 - 5	108-67-8
cumene	1 - 5	98-82-8

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Ingestion** : Get medical attention immediately. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

Most important symptoms/effects, acute and delayed

Potential acute health effects

- Inhalation** : No known significant effects or critical hazards.
- Ingestion** : Harmful if swallowed. May be fatal if swallowed and enters airways.
- Skin contact** : Causes skin irritation.
- Eye contact** : Causes serious eye irritation.

Over-exposure signs/symptoms

- Inhalation** : Adverse symptoms may include the following:
reduced foetal weight
increase in foetal deaths
skeletal malformations
- Ingestion** : Adverse symptoms may include the following:
nausea or vomiting
reduced foetal weight
increase in foetal deaths
skeletal malformations
- Skin** : Adverse symptoms may include the following:
irritation
redness
reduced foetal weight
increase in foetal deaths
skeletal malformations
- Eyes** : Adverse symptoms may include the following:
pain or irritation
watering
redness

Indication of immediate medical attention and special treatment needed, if necessary

- Specific treatments** : Not available.
- Notes to physician** : No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Firefighting measures

Extinguishing media

Suitable : Use dry chemical, CO₂, water spray (fog) or foam.

Not suitable : Do not use water jet.

Specific hazards arising from the chemical : Highly flammable liquid and vapour. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sewer may create fire or explosion hazard. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous thermal decomposition products : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide

Hazchem code : 3YE

Special precautions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).

Environmental precautions : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

Methods and material for containment and cleaning up

Small spill : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor.

Large spill : Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling : Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not get in eyes or on skin or clothing. Do not swallow. Avoid breathing vapour or mist. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately

Section 7. Handling and storage

ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by earthing and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.

Conditions for safe storage, including any incompatibilities : Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
n-butyl acetate	NZ HSWA (New Zealand, 6/2016). WES-TWA: 150 ppm 8 hours. WES-TWA: 713 mg/m ³ 8 hours. WES-STEL: 950 mg/m ³ 15 minutes. WES-STEL: 200 ppm 15 minutes.
xylene	NZ HSWA (New Zealand, 6/2016). Notes: See Notice of Intended Changes. WES-TWA: 217 mg/m ³ , 0 times per shift, 8 hours. WES-TWA: 50 ppm, 0 times per shift, 8 hours.
1,2,4-trimethylbenzene	ACGIH TLV (United States, 3/2016). TWA: 123 mg/m ³ 8 hours. TWA: 25 ppm 8 hours.
acetone	NZ HSWA (New Zealand, 6/2016). WES-TWA: 500 ppm 8 hours. WES-TWA: 1185 mg/m ³ 8 hours. WES-STEL: 2375 mg/m ³ 15 minutes. WES-STEL: 1000 ppm 15 minutes.
ethylbenzene	NZ HSWA (New Zealand, 6/2016). WES-STEL: 543 mg/m ³ 15 minutes. WES-STEL: 125 ppm 15 minutes. WES-TWA: 434 mg/m ³ 8 hours. WES-TWA: 100 ppm 8 hours.
mesitylene	ACGIH TLV (United States, 3/2016). TWA: 123 mg/m ³ 8 hours. TWA: 25 ppm 8 hours.
cumene	NZ HSWA (New Zealand, 6/2016). Absorbed through skin. WES-STEL: 375 mg/m ³ 15 minutes. WES-STEL: 75 ppm 15 minutes. WES-TWA: 125 mg/m ³ 8 hours. WES-TWA: 25 ppm 8 hours.

Appropriate engineering controls : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Section 8. Exposure controls/personal protection

- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
- Individual protection measures**
- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Respiratory protection** : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Recommended: EN 405:2001 + A1:2009 organic vapour filter (Type A) FFA2P3 R D
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. > 8 hours (breakthrough time): Recommended EN 374 polyvinyl alcohol (PVA) ≥ 0.7 mm
< 1 hour (breakthrough time): Conditionally suitable materials for protective gloves; EN 374: Nitrile rubber - NBR (≥ 0.35 mm). Only suitable as splash protection. Only suitable for brief exposure. In the event of contamination, change protective gloves immediately.
- Eye protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles. Recommended: chemical splash goggles and/or face shield.
- Skin protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Recommended: Cotton or cotton/synthetic overalls or coveralls are normally suitable.

Section 9. Physical and chemical properties

Appearance

- Physical state** : Liquid.
- Colour** : Clear.
- Odour** : Not available.
- Odour threshold** : Not available.
- pH** : Not available.
- Melting point** : Not available.
- Boiling point** : $>56^{\circ}\text{C}$ ($>132.8^{\circ}\text{F}$)
- Flash point** : Closed cup: 8.5°C (47.3°F)
- Evaporation rate** : Not available.
- Flammability (solid, gas)** : Not available.
- Lower and upper explosive (flammable) limits** : Not available.
- Vapour pressure** : Not available.
- Vapour density** : Not available.
- Relative density** : 0.86

Section 9. Physical and chemical properties

Solubility : Insoluble in the following materials: cold water and hot water.

Partition coefficient: n-octanol/water : Not available.

Auto-ignition temperature : 350°C (662°F)

Decomposition temperature : Not available.

Viscosity : Kinematic (40°C (104°F)): 0.06 cm²/s (6 cSt)

Aerosol product

Type of aerosol : Not applicable.

Heat of combustion : Not available.

Ignition distance : Not applicable.

Enclosed space ignition - Time equivalent : Not applicable.

Enclosed space ignition - Deflagration density : Not applicable.

Flame height : Not applicable.

Flame duration : Not applicable.

Section 10. Stability and reactivity

Chemical stability : The product is stable.

Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : Avoid all possible sources of ignition (spark or flame). Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.

Incompatible materials : Reactive or incompatible with the following materials:
oxidizing materials

Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on likely routes of exposure

Inhalation : No known significant effects or critical hazards.

Ingestion : Harmful if swallowed. May be fatal if swallowed and enters airways.

Skin contact : Causes skin irritation.

Eye contact : Causes serious eye irritation.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation : Adverse symptoms may include the following:
reduced foetal weight
increase in foetal deaths
skeletal malformations

Ingestion : Adverse symptoms may include the following:
nausea or vomiting
reduced foetal weight
increase in foetal deaths
skeletal malformations

Skin contact : Adverse symptoms may include the following:
irritation
redness
reduced foetal weight
increase in foetal deaths
skeletal malformations

Section 11. Toxicological information

Eye contact : Adverse symptoms may include the following:
 pain or irritation
 watering
 redness

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
n-butyl acetate	LC50 Inhalation Vapour	Rat	>21.1 mg/l	4 hours
	LD50 Dermal	Rabbit	>14112 mg/kg	-
	LD50 Oral	Rat	10760 mg/kg	-
Solvent naphtha (petroleum), light arom.	LC50 Inhalation Vapour	Rat	>6193 mg/l	4 hours
	LD50 Dermal	Rabbit	>3160 mg/kg	-
	LD50 Oral	Rat	3492 mg/kg	-
xylene	LC50 Inhalation Vapour	Rat	27.6 mg/l	4 hours
	LD50 Dermal	Rabbit	>2000 mg/kg	-
	LD50 Oral	Rat	>2000 mg/kg	-
1,2,4-trimethylbenzene acetone	LD50 Oral	Rat	>5000 mg/kg	-
	LC50 Inhalation Vapour	Rat	76 mg/l	4 hours
	LD50 Dermal	Rabbit	>15800 mg/kg	-
Solvent naphtha (petroleum), heavy arom.	LD50 Oral	Rat	5800 mg/kg	-
	LC50 Inhalation Vapour	Rat	>4688 mg/m ³	4 hours
	LD50 Dermal	Rabbit	>2000 mg/kg	-
ethylbenzene	LD50 Oral	Rat	>5000 mg/kg	-
	LC50 Inhalation Vapour	Rat	>9.6 mg/l	4 hours
	LD50 Dermal	Rabbit	>15000 mg/kg	-
cumene	LD50 Oral	Rat	>3500 mg/kg	-
	LC50 Inhalation Vapour	Rat	39000 mg/m ³	4 hours
	LD50 Oral	Rat	1400 mg/kg	-

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
xylene	Skin - Mild irritant	Rat	-	8 hours 60 microliters	-
	Skin - Moderate irritant	Rabbit	-	24 hours 500 milligrams	-
	Skin - Moderate irritant	Rabbit	-	100 Percent	-
	Eyes - Mild irritant	Rabbit	-	87 milligrams	-
	Eyes - Severe irritant	Rabbit	-	24 hours 5 milligrams	-
acetone	Eyes - Mild irritant	Human	-	186300 parts per million	-
	Eyes - Mild irritant	Rabbit	-	10 microliters	-
	Eyes - Moderate irritant	Rabbit	-	24 hours 20 milligrams	-
	Eyes - Severe irritant	Rabbit	-	20 milligrams	-
	Skin - Mild irritant	Rabbit	-	24 hours 500 milligrams	-
Solvent naphtha (petroleum), heavy arom. ethylbenzene	Skin - Mild irritant	Rabbit	-	395 milligrams	-
	Skin - Mild irritant	Rabbit	-	24 hours 500 microliters	-
	Eyes - Severe irritant	Rabbit	-	500 milligrams	-
mesitylene	Skin - Mild irritant	Rabbit	-	24 hours 15 milligrams	-
	Eyes - Mild irritant	Rabbit	-	24 hours 500 milligrams	-
	Skin - Moderate irritant	Rabbit	-	24 hours 20 milligrams	-
cumene	Eyes - Mild irritant	Rabbit	-	24 hours 500 milligrams	-

Section 11. Toxicological information

	Eyes - Mild irritant	Rabbit	-	milligrams	
	Skin - Mild irritant	Rabbit	-	86 milligrams	-
				24 hours 10	-
	Skin - Moderate irritant	Rabbit	-	milligrams	
				24 hours 100	-
				milligrams	

Sensitisation

Not available.

Potential chronic health effects

General : No known significant effects or critical hazards.

Inhalation : No known significant effects or critical hazards.

Ingestion : No known significant effects or critical hazards.

Skin contact : No known significant effects or critical hazards.

Eye contact : No known significant effects or critical hazards.

Carcinogenicity : Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.

Mutagenicity : No known significant effects or critical hazards.

Teratogenicity : Suspected of damaging the unborn child.

Developmental effects : No known significant effects or critical hazards.

Fertility effects : Suspected of damaging fertility.

Chronic toxicity

Not available.

Carcinogenicity

Not available.

Mutagenicity

Not available.

Teratogenicity

Not available.

Reproductive toxicity

Not available.

Specific target organ toxicity

Name	Category	Route of exposure	Target organs
xylene	Category B	Oral Inhalation	Not determined Not determined
1,2,4-trimethylbenzene	Category B	Inhalation	Not determined
ethylbenzene	Category B	Inhalation	Not determined
cumene	Category B	Inhalation	Not determined

Aspiration hazard

Name
Solvent naphtha (petroleum), light arom. Solvent naphtha (petroleum), heavy arom.

Numerical measures of toxicity

Acute toxicity estimates

Route	ATE value
Oral	1944.5 mg/kg
Dermal	8379 mg/kg
Inhalation (vapours)	20.59 mg/l

Section 12. Ecological information

Ecotoxicity : Water polluting material. May be harmful to the environment if released in large quantities. This material is toxic to aquatic life with long lasting effects.

Aquatic and terrestrial toxicity

Product/ingredient name	Result	Species	Exposure
n-butyl acetate	Acute EC50 397 mg/l	Algae - Selenastrum capricornutum	72 hours
	Acute EC50 44 mg/l	Daphnia - Daphnia magna	48 hours
	Acute LC50 32 mg/l	Crustaceans - Artemia salina	48 hours
	Acute LC50 18 mg/l	Fish - Pimephales promelas	96 hours
	Acute NOEC 200 mg/l	Algae	72 hours
Solvent naphtha (petroleum), light arom.	Acute EC50 2.9 mg/l	Algae - Pseudokirchneriella subcapitata	72 hours
	Acute EC50 3.2 mg/l	Daphnia - Daphnia magna	48 hours
	Acute LC50 9.2 mg/l	Fish - Oncorhynchus mykiss	96 hours
	Acute NOEC >1 mg/l	Algae - Pseudokirchneriella subcapitata	72 hours
xylene	Acute EC50 1 to 10 mg/l	Algae	72 hours
	Acute EC50 1 to 10 mg/l	Daphnia - Daphnia magna	48 hours
	Acute LC50 1 to 10 mg/l	Fish	96 hours
1,2,4-trimethylbenzene	Acute EC50 1 to 10 mg/l	Fish	96 hours
acetone	Acute EC50 8800 mg/l	Daphnia - Daphnia pulex	48 hours
	Acute LC50 5540 mg/l	Fish - Oncorhynchus mykiss	96 hours
	Acute NOEC 430 mg/l	Algae	96 hours
	Chronic NOEC 2212 mg/l	Daphnia - Daphnia pulex	28 days
Solvent naphtha (petroleum), heavy arom.	Acute EC50 11 mg/l	Algae - Pseudokirchneriella subcapitata	72 hours
	Acute EC50 3 to 10 mg/l	Daphnia - Daphnia magna	48 hours
	Acute LC50 2 to 5 mg/l	Fish - Oncorhynchus mykiss	96 hours
ethylbenzene	Acute EC50 >1.8 mg/l	Daphnia - Daphnia magna	48 hours
	Acute LC50 >10 mg/l	Fish - Pimephales promelas	96 hours
cumene	Acute EC50 2600 µg/l Fresh water	Algae - Pseudokirchneriella subcapitata	72 hours
	Acute EC50 7400 to 11290 µg/l Fresh water	Crustaceans - Artemia sp. - Nauplii	48 hours
	Acute EC50 10600 to 14100 µg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 2700 µg/l Fresh water	Fish - Oncorhynchus mykiss	96 hours

Persistence/degradability

Product/ingredient name	Test	Result	Dose	Inoculum
n-butyl acetate	OECD 301D Ready Biodegradability - Closed Bottle Test	>80 % - 5 days	-	-
Solvent naphtha (petroleum), light arom.	-	78 % - Readily - 28 days	-	Fresh water
Solvent naphtha (petroleum), heavy arom.	-	50 % - Readily - 28 days	-	Fresh water

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
n-butyl acetate	-	-	Readily
Solvent naphtha (petroleum), light arom.	-	-	Readily
Solvent naphtha (petroleum), heavy arom.	-	-	Readily

Bioaccumulative potential

Section 12. Ecological information

Product/ingredient name	LogP _{ow}	BCF	Potential
n-butyl acetate	2.3	-	low
xylene	3.12	8.1 to 25.9	low
1,2,4-trimethylbenzene	3.63	243	low
acetone	-0.23	-	low
ethylbenzene	3.6	-	low
mesitylene	3.42	161	low
cumene	3.55	94.69	low

Mobility in soil





Soil/water partition coefficient (K_{oc}) : Not available.

Other adverse effects : No known significant effects or critical hazards.






Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label	Additional information
New Zealand Class	UN1263	PAINT RELATED MATERIAL	3	II	 	<p>The marine pollutant mark is not required when transported by road or rail.</p> <p>Hazchem code 3YE</p> <p>Special provisions 163</p>
ADG Class	UN1263	PAINT RELATED MATERIAL	3	II		<p>Hazchem code •3YE</p> <p>Special provisions 163</p>
UN Class	UN1263	PAINT RELATED MATERIAL	3	II		<p>Special provisions 163</p>

Section 14. Transport information

ADR/RID Class	UN1263	PAINT RELATED MATERIAL	3	II	 	<p>The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg.</p> <p><u>Hazard identification number</u> 33</p> <p><u>Limited quantity</u> 5 L</p> <p><u>Special provisions</u> 163, 640C, 650</p> <p><u>Tunnel code</u> (D/E)</p>
IATA Class	UN1263	Paint related material	3	II		<p>The environmentally hazardous substance mark may appear if required by other transportation regulations.</p> <p><u>Passenger and Cargo Aircraft</u> Quantity limitation: 5 L Packaging instructions: 353</p> <p><u>Cargo Aircraft Only</u> Quantity limitation: 60 L Packaging instructions: 364</p> <p><u>Limited Quantities - Passenger Aircraft</u> Quantity limitation: 1 L Packaging instructions: Y341</p> <p><u>Special provisions</u> A3, A72</p>
IMDG Class	UN1263	PAINT RELATED MATERIAL	3	II	 	<p>The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg.</p> <p><u>Emergency schedules (EmS)</u> F-E, _S-E_</p> <p><u>Special provisions</u> 163</p>

PG* : Packing group

Section 15. Regulatory information

- New Zealand Inventory of Chemicals (NZIoC)** : All components are listed or exempted.
- HSNO Approval Number** : HSR002652
- HSNO Group Standard** : Solvents
- HSNO Classification** : 3.1 - FLAMMABLE LIQUIDS - Category B
 6.1 - ACUTE TOXICITY (oral) - Category D
 6.3 - SKIN IRRITATION - Category A
 6.4 - EYE IRRITATION - Category A (Irritant)
 6.7 - CARCINOGENICITY - Category B
 6.8 - REPRODUCTIVE AND DEVELOPMENTAL TOXICITY (Fertility) - Category B
 6.8 - REPRODUCTIVE AND DEVELOPMENTAL TOXICITY (Unborn child) - Category B
 6.9 - SPECIFIC TARGET ORGAN TOXICITY (SINGLE OR REPEATED EXPOSURE) - Category B
 6.1 - ACUTE TOXICITY (aspiration) (oral) - Category E
 9.1 - AQUATIC ECOTOXICITY - Category B

Australia inventory (AICS) : All components are listed or exempted.

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol (Annexes A, B, C, E)

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

International lists

National inventory

- Australia** : All components are listed or exempted.
- Canada** : All components are listed or exempted.
- China** : All components are listed or exempted.
- Europe** : All components are listed or exempted.
- Japan** : **Japan inventory (ENCS)**: Not determined.
Japan inventory (ISHL): Not determined.
- Malaysia** : All components are listed or exempted.
- Philippines** : All components are listed or exempted.
- Republic of Korea** : All components are listed or exempted.
- Taiwan** : All components are listed or exempted.
- Turkey** : All components are listed or exempted.
- United States** : All components are listed or exempted.

Section 16. Other information

History

- Date of printing** : 22/09/2017
- Date of issue/Date of revision** : 22/09/2017
- Date of previous issue** : 06/06/2017
- Version** : 1

Section 16. Other information

Key to abbreviations

: ADG = Australian Dangerous Goods
ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
IATA = International Air Transport Association
IBC = Intermediate Bulk Container
IMDG = International Maritime Dangerous Goods
LogPow = logarithm of the octanol/water partition coefficient
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
UN = United Nations

References

: Not available.

✔ Indicates information that has changed from previously issued version.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.